

Mini Glee

- Die cast aluminium trim
- Polycarbonate secondary optics with various color options
- CREE version available
- Separate order of LED driver available




Non-adjustable Version

MX7484 - G5 - ☐ ☐ ☐ - ☐ ☐ ☐ - ☐ ☐ ☐

Code	CRI	Code	CCT	Code	Beam Angle	Code	Color
8	80	27	2700K	15	15°	82	White Trim & Black Reflector
9	90	30	3000K	30	30°	84	White Trim & Silver Reflector
		35	3500K	50	50°	86	White Trim & Sandblasted Reflector
		40	4000K			89	White Trim & Rose Gold Reflector

7.5W 200mA 845lm CRI80

7.5W 200mA 710lm CRI90






Ø64


Ø59




Color



MX 7484-G5-830-15



MX 7484-G5-830-30



MX 7484-G5-830-50


Wallwasher Version

MX7485 - G5 - ☐ ☐ ☐ - **NA - 84**

Code	CRI	Code	CCT
8	80	27	2700K
9	90	30	3000K
		35	3500K
		40	4000K

7.5W 200mA 845lm CRI80

7.5W 700mA 710lm CRI90



Ø64

Ø59



LED Driver

Ordering Code	Driving Power Range	Matching with LED Fitting	Output Current	Wiring Box Dimension(mm) (L) x (W) x (H)	Cut Hole (mm)
EC LED-200mA-8-ER(02)	6.6-7.5W	COB Module 7.5W	200mA	140 x 45 x 30	Ø52
EC LED-SETmA-M12D-LT(36)	2.2-7.5W		200mA, 1-10V Dimmable	220 x 45 x 30	Ø56