

Glee

- Die cast aluminium trim
- Polycarbonate secondary optics with various color options
- Xicato, COB and MR16 retrofit version available
- Separate order of LED driver available





Non-adjustable Version

MX 7488 - G5 - ☐ ☐ - ☐ ☐ - ☐ ☐


Code	CRI	Code	CCT	Code	Beam Angle	Code	Color
8	80	27	2700K	18	18°	82	White Trim & Black Reflector
9	90	30	3000K	23	23°	84	White Trim & Silver Reflector
		35	3500K	36	36°	86	White Trim & Sandblasted Reflector
		40	4000K			89	White Trim & Rose Gold Reflector

13.8W 500mA 1663lm, CRI80 COB LED


13.8W 500mA 1375lm, CRI90 COB LED



MX 7488-G5-830-18



MX 7488-G5-830-23





MX 7488-G5-830-36

FreePlus Version

MX 7480 - - ☐ ☐

*Please refer to P.13-17 for the FreePlus Module Matrix

Code	Color
82	White Trim & Black Reflector
84	White Trim & Silver Reflector
86	White Trim & Sandblasted Reflector
89	White Trim & Rose Gold Reflector




Refer to FreePlus Module for photometrix

MR16 Version

MX 5474 - M - ☐ ☐

Code	Color
82	White Trim & Black Reflector
84	White Trim & Silver Reflector
86	White Trim & Sandblasted Reflector
89	White Trim & Rose Gold Reflector

1 x GU 5.3 Max 15W or LED Retrofit MR16



LED Driver

Ordering Code	Driving Power Range	Matching with LED Fitting	Output Current	Wiring Box Dimension(mm) (L) x (W) x (H)	Cut Hole (mm)
EC LED-500mA-20-AC(19)	2-18W	COB Module 13.8W	500mA	220 x 66 x 38	Ø76
EC LED-SETmA-M20D-MIAM-TCI(19)	1-18W		500mA, 1-10V Dimmable		

